

Ally Fire Nozzles Selectable Litreage Nozzles

Features

- High strength aluminium construction with trademark Nituff finish (50 microns of PTFE impregnated hard-coated finish)
- For high pressure application up to 580 PSI (40 Bar)
- Constant flow selectable litreage nozzle with multiple flow settings
- Selected flow remains constant regardless of pattern change
- 1/4 turn for quick change from straight stream to fog
- Integrated stream shaper to enhance performance
- Combination of fog and straight stream
- Superb wide fog pattern for optimum personal protection
- Flush without changing pattern or shutting down
- Conforms to all aspects of NFPA 1964 (spray nozzles, shutoff and tips) 2008 edition

STYLE	INLET	FLOW RATE @100PSI (6.9 BAR)	LENGTH	WEIGHT
710	25mm NH, BSP or Instaneous Male to BS336	19-37-90-150 LPM	191mm	1.1kg
711		50-100-150-230 LPM		
712		50-90-115 LPM		
715	38mm	115-230-360-475 LPM	228mm	1.9kg



ALL HOSE & VALVES

- Phone: 07 3205 6433 Fax 07 3205 4844
- Email sales@allhose.com.au www.allhose.com.au





Ally Fire Nozzles

Selectable Litreage Nozzles





ALL HOSE & VALVES • Phone: 07 3205 6433 • Fax 07 3205 4844

Email sales@allhose.com.au • www.allhose.com.au