

Bettaflo Canvas Fire Hose


Hose Construction

Jacket: 100% Polyester jacket,

single jacket, twill weave

NON-PERC DN38×30M CLASS H AS2792 SN Lining: EPDM tube vulcanised twice

Colour: White



DIAMETER	38mm / 1.1/2"	64mm / 2.1/2"
WORKING PRESSURE	17 Bar	17 Bar
BURST PRESSURE	51 Bar	51 Bar

PACKAGING: Packed in carton or loaded onto a pallet

StandardsMark Licence

Manufactured to:

AS 2792-1992 - Fire hose - Delivery layflat

"the StandardsMark Licensee" the right to use the STANDARDSMARK as shown below only in respect of the goods described and detailed in the Schedule which are produced by the Licensee or on behalf of the Licensee* and which comply with the appropriate Standard referred to above as from time to time amended. The Licence is granted subject to the rules governing the use of the STANDARDSMARK and the Terms and Conditions for certification and licence. The Licensee covenants to comply with all the Rules and Terms and Conditions.

Certificate No:SMK40657

Issued: 5 March 2018 Expires: 16 January 2023 Originally Certified: 17 January 2018 Current Certification: 5 March 2018



Nicole Grantham General Manager SAI Global Certification Services







ALL HOSE & VALVES

Phone: 07 3205 6433
Fax 07 3205 4844

Email sales@allhose.com.au • www.allhose.com.au