



ALL HOSE & VALVES

Bettaflo Extruded Fire Hose

Hose Features

- Durable, Abrasion Resistant
- Good UV resistance
- Resistant to oil, petrol and a wide range of chemicals
- No drying required, just wipe down after an incident
- Low friction loss due to hose construction



Hose Construction

- Nitrile Rubber/PVC Blend Tube
- Reinforcement, Synthetic Yarn
- Heavy Rib
- High Abrasion Resistance



Available Hose Diameters

- Hose available in diameters 25mm up to 306mm

Applications

- Industrial fire fighting, water discharge, de-watering applications

Colour

- Available all sizes in Red and Yellow (38mm only)



ALL HOSE & VALVES

- Phone: 07 3205 6433 • Fax 07 3205 4844
- Email sales@allhose.com.au • www.allhose.com.au



ALL HOSE & VALVES

Bettaflo Extruded Fire Hose

Hose Specifications

StandardsMark Licence

Manufactured to:

AS 2792-1992 - Fire hose - Delivery layflat

"the StandardsMark Licensee" the right to use the STANDARDSMARK as shown below only in respect of the goods described and detailed in the Schedule which are produced by the Licensee or on behalf of the Licensee* and which comply with the appropriate Standard referred to above as from time to time amended. The Licence is granted subject to the rules governing the use of the STANDARDSMARK and the Terms and Conditions for certification and licence. The Licensee covenants to comply with all the Rules and Terms and Conditions.

Certificate No: SMK40657

Issued: 5 March 2018

Originally Certified: 17 January 2018

Expires: 16 January 2023

Current Certification: 5 March 2018

Nicole Grantham
General Manager SAI Global Certification Services



BETTAFLO Extruded Fire Hose – AS2792-1992 Class H – Certificate No: SMK40657

DIAMETER	mm/ inch	25mm / 1"	38mm / 1.1/2"	45mm / 1.3/4"	51mm / 2"	64mm / 2.1/2"
WEIGHT PER METRE	kg / metre	0.21	0.32	0.36	0.43	0.54
COLOUR STANDARD	Red / Yellow	Red	Red / Yellow	Red	Red	Red
COIL STANDARD	metre	30	30	30	30	30
COIL DIAMETER / 30 METRE	cm	47cm	47cm	48cm	49cm	49cm
STANDARD WORKING PRESSURE	kPa	2100	2100	2100	2100	2100
BURST PRESSURE	kPa	5250	5250	5250	5250	5250
NOMINAL SAFETY RATIO		3 to 1	3 to 1	3 to 1	3 to 1	3 to 1
TEMPERATURE RANGE	Cdg	-20°C - 80°C	-20°C - 80°C	-20°C - 80°C	-20°C - 80°C	-20°C - 80°C

COVER AND TUBE: Nitrile / PVC blend tube, heavy rib with high abrasion resistance

PACKAGING: Single rolled hose pack in carton



ALL HOSE & VALVES

- Phone: 07 3205 6433 • Fax 07 3205 4844
- Email sales@allhose.com.au • www.allhose.com.au