



TPR Ducting

TUBE: Black EPDM/PP fully recyclable and Halogens/Phtalates free.

REINFORCEMENT: Steel helix wire.

APPLICATION: Hot air, gas, fume extraction - ventilation ducting wher high temperature resistance is required.

TEMPERATURE RANGE: -40°C to +120°C



SIZE	ID	BEND RADIUS	COIL	CODE
2	51.0	40mm	10	DUCTTPR051
2 ½	63.5	55mm	10	DUCTTPR063
3	76.0	65mm	10	DUCTTPR076
3 ½	90.0	75mm	10	DUCTTPR090
4	102.0	85mm	10	DUCTTPR100
5	127.0	105mm	10	DUCTTPR125
6	152.0	125mm	10	DUCTTPR150
7	178.0	150mm	10	DUCTTPR178
8	203.0	165mm	10	DUCTTPR200

PU Vulcano Ducting

TUBE: Clear PU.

REINFORCEMENT: Steel helix wire.

APPLICATION: Suction of pellets, granulates, abrasive powders and chemicals. In ceramic, suction plants, woodworking and plastic industry.

TEMPERATURE RANGE: -40°C to +90°C



SIZE	ID	BEND RADIUS	COIL	CODE
1 ½	38.0	30mm	10	DUCTPU-V-038
2	51.0	40mm	10	DUCTPU-V-051
2 ½	63.5	55mm	10	DUCTPU-V-063
3	76.0	65mm	10	DUCTPU-V-076
4	102.0	85mm	10	DUCTPU-V-102
5	127.0	105mm	10	DUCTPU-V-127
6	152.0	125mm	10	DUCTPU-V-152
7	178.0	150mm	10	DUCTPU-V-178
8	203.0	165mm	10	DUCTPU-V-203



Plastiflex Ducting - Grey

TUBE: Clear PU.

REINFORCEMENT: Steel helix wire.

APPLICATION: Suction of pellets, granulates, abrasive powders and chemicals. In ceramic, suction plants, woodworking and plastic industry.

TEMPERATURE RANGE: -40°C to +90°C



SIZE	ID	BEND RADIUS	COIL	CODE
1 ½	38.0	80mm	10	DUCTPLAS038
2	51.0	102mm	10	DUCTPLAS051
2 ¼	57.0	114mm	10	DUCTPLAS057
2 ½	63.0	126mm	10	DUCTPLAS063
3	76.0	152mm	10	DUCTPLAS076
3 ½	89.0	178mm	10	DUCTPLAS089
4	102.0	204mm	10	DUCTPLAS102
4 ½	114.0	228mm	10	DUCTPLAS114
5	127.0	254mm	10	DUCTPLAS127
6	152.0	304mm	10	DUCTPLAS152
7	178.0	356mm	10	DUCTPLAS178
8	203.0	406mm	10	DUCTPLAS203
10	254.0	508mm	10	DUCTPLAS254
12	305.0	610mm	10	DUCTPLAS305