



Tigertail Suction

A robust suction and discharge hose well suited for use in extreme environments, its high nitrile / PVC compound gives this hose excellent flexibility and UV stability. It is especially well suited for use with abrasive slurries, on waste trucks, for many chemicals plus high volume air seeder applications.

Operating Temperature from -5°C to +60°C.




SIZE	ID	OD	PRESSURE @ 20°C (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
2	50.0	63.4	73	230	350mm	20	PVCTSH050
2 ½	63.0	79.6	58	230	380mm	20	PVCTSH065
3	76.0	93.4	58	230	400mm	20	PVCTSH080
4	102.0	118.0	43	230	600mm	20	PVCTSH100

Kaneline Suction

Heavy duty suction and discharge hose for use in the rental/construction pumping and general water transfer. High tensile textile cord with orange anti-shock rigid PVC helix. Clear smooth PVC - abrasive resistant. Clear corrugated PVC - abrasive resistant.

Operating Temperature from -25°C to +65°C



SIZE	ID	OD	PRESSURE (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
2	51.0	66.0	100	29	102mm	20	PVCKORS050
2 ½	63.0	79.6	100	28	130mm	20	PVCKORS080
3	76.0	94.0	100	28	152mm	20	PVCKORS100

Grey Suction Hose

A premium quality general purpose hose with excellent flexibility in its class. Particularly well suited for use with water, mud, grain, sand and some chemicals. Hose has very good abrasion resistance and excellent UV stability. Hose conforms to AS/NZS 2070.

Operating Temperature from -5°C to +60°C.




SIZE	ID	OD	PRESSURE @ 20°C (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
1	25.0	31.9	130	624	120mm	20	PVCGSH025
1 ¼	32.0	39.4	116	624	150mm	20	PVCGSH032
1 ½	38.0	46.1	101	624	200mm	20	PVCGSH038
2	50.0	60.2	87	624	300mm	20	PVCGSH050
2 ½	63.0	74.4	87	624	400mm	20	PVCGSH065
3	76.0	88.0	73	624	450mm	20	PVCGSH080
4	102.0	116.0	58	624	600mm	20	PVCGSH100

Blue Nitrile Suction Hose

An extremely flexible hose particularly well suited for collection of environmental waste products and chemicals. Its high nitrile / PVC compound gives this hose improved resistance to mineral oils and animal fats as well as reducing compression set. This makes it ideal for grease trap & septic tank applications especially in colder weather. Its has enhanced UV stability.

Operating Temperature from -5°C to +60°C.



SIZE	ID	OD	PRESSURE @ 20°C (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
1	25.0	31.9	130	624	120mm	20	PVCBSH025
1 ¼	32.0	39.4	116	624	150mm	20	PVCBSH032
1 ½	38.0	46.1	101	624	200mm	20	PVCBSH038
2	50.0	60.2	87	624	300mm	20	PVCBSH050
2 ½	63.0	74.4	87	624	400mm	20	PVCBSH065
3	76.0	89.6	73	624	450mm	20	PVCBSH080
4	102.0	116.0	58	624	600mm	20	PVCBSH100



ALL HOSE & VALVES
BRENDALE • CABOOLTURE • GOLD COAST

EST. 2008

HOSE - PVC SUCTION

Marineflex

A smooth bore lightweight hose with excellent flexibility. Particularly well suited for use on bilge pumps or a waste hose for caravans and RV's. Hose is also suitable for dust extraction, cable conduit and light duty Air Seeder applications. Hose has excellent UV stability.

Operating Temperature from -5°C to +60°C.



SIZE	ID	OD	PRESSURE (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
3/4	19.0	24.7	29	310	90mm	20/30	PVCBSH025
1	32.0	39.4	29	310	95mm	20/30	PVCBSH032
1 1/8	38.0	46.1	29	310	105mm	20	PVCBSH038
1 1/4	50.0	60.2	29	310	115mm	20	PVCBSH050
1 1/2	63.0	74.4	29	310	140mm	20	PVCBSH065
2	76.0	89.6	29	310	180mm	20	PVCBSH080

Helisteel

A smooth bore lightweight hose with excellent flexibility. Particularly well suited for use on bilge pumps or a waste hose for caravans and RV's. Hose is also suitable for dust extraction, cable conduit and light duty Air Seeder applications. Hose has excellent UV stability.

Operating Temperature from -5°C to +60°C.



SIZE	ID	OD	PRESSURE (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
1/2	13.0	18.0	72	27	60mm	20,60	PVCHSH012
5/8	16.0	23.0	72	27	90mm	20,60	PVCHSH016
3/4	19.0	27.0	72	27	110mm	20,60	PVCHSH020
1	25.0	31.9	58	27	140mm	20,60	PVCHSH025
1 1/4	32.0	39.4	58	24	160mm	20,60	PVCHSH032
1 1/2	38.0	46.1	58	24	180mm	20,60	PVCHSH040
2	50.0	60.2	58	23	280mm	20,60	PVCHSH050
2 1/2	63.0	74.4	52	23	340mm	20	PVCHSH065
3	76.0	89.6	52	20	410mm	20	PVCHSH080
4	102.0	116.0	34	20	640mm	20	PVCHSH100
6	152.0	170.0	17	20	760mm	20	PVCHSH150

Sanitation

A smooth bore hose with excellent flexibility for use as a toilet waste hose for marine applications. Manufactured from a high nitrile content PVC blend.

The high nitrile content gives this hose excellent resistance to odour permeation for toilet applications.

Operating Temperature from -5°C to +60°C.




SIZE	ID	OD	PRESSURE @ 20°C (PSI)	VAC RATING mm hg	BEND RADIUS	COIL	CODE
3/4	19.0	25.8	131	624	110mm	20	PVCMSH020
1	25.0	31.9	131	624	120mm	20	PVCMSH025
1 1/2	38.0	46.1	87	624	200mm	20	PVCMSH040

Air Seeder

For use as secondary and tertiary lines on airseeder machines. Rigid EVA spiral inner tube and black smooth EVA cover. UV stabilised with good abrasion resistance.

Operating Temperature from -5°C to +60°C.



SIZE	ID	OD	COIL	CODE
1	25.0	32.0	20	PVCASH025
1 1/4	31.5	41.0	20	PVCASH032
1 1/2	38.0	47.0	20	PVCASH040
2	50.0	64.0	20	PVCASH050
2 1/2	63.0	76.0	20	PVCASH065
3	76.0	87.0	20	PVCASH080